

View Online at <https://aerobasegroup.com/nsn/5950-00-648-6136>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.740 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.740 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.250 inches

Body Width:

2.250 inches

Body Height:

2.750 inches

End Application:

Aircraft, phantom f-4; submarine auxillary and miscellaneous systems; aircraft, eagle f-15; trident hull structure; radar and iff systems; communications and data systems; ssbn mk-118 fire control sys; navigational systems; ship, ohio class ssn (trident); aircraft, hercules c-130

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

3.0 amperes ac single component 2nd secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0