

View Online at <https://aerobasegroup.com/nsn/5950-00-648-6146>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.906 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.781 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded and brought out to primary terminal single component

Body Length:

2.500 inches

Body Width:

2.375 inches

Body Height:

2.813 inches

Inclosure Type:

Hermetically sealed with oil

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

25.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Special Features:

1 primary, 5 secondaries

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

22 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0