

View Online at <https://aerobasegroup.com/nsn/5950-00-648-6285>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.250 inches single mounting facility single center group

**Frequency Rating:**

350.0 hertz single component and 450.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

4.375 inches

**Body Width:**

3.750 inches

**Body Height:**

5.000 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Special Features:**

Xcase metal material, 0.812 in. O/a h of terminals, shield w/one standoff solder terminal, primary winding 117 v rating, secondary winding rated 5 v at 2 amp, 6.3 v at 600 ma, 6.3 v at 4.5 amp, 6.3 v at 4.5 amp, 608 v at 157 ma w/center tap

**Terminal Type And Quantity:**

13 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0