

View Online at <https://aerobasegroup.com/nsn/5950-00-648-6285>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.250 inches single mounting facility single center group

Frequency Rating:

350.0 hertz single component and 450.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.375 inches

Body Width:

3.750 inches

Body Height:

5.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Special Features:

Xcase metal material, 0.812 in. O/a h of terminals, shield w/one standoff solder terminal, primary winding 117 v rating, secondary winding rated 5 v at 2 amp, 6.3 v at 600 ma, 6.3 v at 4.5 amp, 6.3 v at 4.5 amp, 608 v at 157 ma w/center tap

Terminal Type And Quantity:

13 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0