NSN 5950-00-648-6667

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-6667

| Reliability I | ndicator: |
|---------------|-----------|
|---------------|-----------|

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.188 inches

Body Width:

2.000 inches

Body Height:

1.781 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

3.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

38.30 ac volts single component 4th secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5950-00-648-6667

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0