

View Online at <https://aerobasegroup.com/nsn/5950-00-648-6669>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches single mounting facility single center group

Frequency Rating:

350.0 hertz single component and 450.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.875 inches

Body Width:

1.875 inches

Body Height:

2.438 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

150.0 milliamperes ac single component single secondary

Winding Operating Voltage:

3.00 ac volts single component single secondary and 10.00 ac volts single component single secondary and 26.00 ac volts single component single secondary and 57.00 ac volts single component single secondary and 78.00 ac volts single component single secondary and 115.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0