NSN 5950-00-648-6669Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-6669
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.312 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.312 inches single mounting facility single center group
Frequency Rating:
350.0 hertz single component and 450.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
1.875 inches
Body Width:
1.875 inches
Body Height:
2.438 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
150.0 milliamperes ac single component single secondary
Winding Operating Voltage:
3.00 ac volts single component single secondary and 10.00 ac volts single component single secondary and 26.00 ac volts single
component single secondary and 57.00 ac volts single component single secondary and 78.00 ac volts single component single secondar
and 115.00 ac volts single component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
9 standoff, solder lug
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5950-00-648-6669

Power Transformer - Page 2 of 2



Fiig:

A058b0