

View Online at <https://aerobasegroup.com/nsn/5950-00-648-6736>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component and 70.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

4.375 inches

**Body Width:**

3.125 inches

**Body Height:**

5.250 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Special Features:**

Case metal material, primary winding 115 v rating, secondary windings rated 5 v at 3 amp, 6.3 v at 600 ma, 6.3 v at 8.5 amp, 650 v at 200 ma w/center tap, 800 v at 5 ma 2.5 v

**Terminal Type And Quantity:**

13 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0