

View Online at <https://aerobasegroup.com/nsn/5950-00-648-6880>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.510 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.890 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.810 inches

Body Width:

2.000 inches

Body Height:

2.380 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

56.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

8.00 ac volts single component 2nd secondary and 26.00 ac volts single component 2nd secondary and 40.00 ac volts single component 2nd secondary and 115.00 ac volts single component 2nd secondary and 300.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0