

View Online at <https://aerobasegroup.com/nsn/5950-00-648-6888>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.500 inches

Body Width:

3.000 inches

Body Height:

2.500 inches

End Application:

Forrestal class cv; kidd class ddg; iwo jima class lph; general purpose electronic test equipment gpete; kilauea class t-ae 26; sturgeon class ssn (637); los angeles class ssn (688); integrated underwater surveillance systems; virginia class cgn (41)

Inclosure Type:

Partially enclosed, half shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

30.0 milliamperes ac single component 2nd secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

600.00 ac volts single component 2nd secondary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0