

View Online at <https://aerobasegroup.com/nsn/5950-00-648-6888>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component and 1.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

2.500 inches

**Body Width:**

3.000 inches

**Body Height:**

2.500 inches

**End Application:**

Forrestal class cv; kidd class ddg; iwo jima class lph; general purpose electronic test equipment gpete; kilauea class t-ae 26; sturgeon class ssn (637); los angeles class ssn (688); integrated underwater surveillance systems; virginia class cgn (41)

**Inclosure Type:**

Partially enclosed, half shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

2 primary single component and 2 secondary single component

**Thread Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

30.0 milliamperes ac single component 2nd secondary

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

600.00 ac volts single component 2nd secondary

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0