NSN 5950-00-648-7113

Current Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-648-7113

| Reliability Indicator: |
|--|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 7.437 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.063 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 12.125 inches |
| Body Width: |
| 5.125 inches |
| Body Height: |
| 5.750 inches |
| Installation For Which Designed: |
| Indoor nonportable |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 6 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 3 primary single component and 3 secondary single component |
| Winding Operating Current: |
| 86.0 amperes ac single component all primary |
| Winding Operating Voltage: |
| 450.00 ac pounds per hour with retaining chain single component single primary |
| Special Features: |
| Inside mtg holes 3.625 in. From holes on one end and 3.812 in. From holes on other end, c/o 3 inseparable current transformers |
| Terminal Type And Quantity: |
| 4 terminal block w/screws and 4 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A058b0