# NSN 5950-00-649-8343

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-649-8343

Reliability	Indicator:
-------------	------------

Not established

#### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.750 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.688 inches single mounting facility single center group

**Overall Height:** 

3.437 inches

**Inductance Type:** 

Fixed

**Inductance Rating:** 

100.00 millihenries single component single winding

Frequency Rating:

114.0 hertz single component and 840.0 hertz single component

**Body Length:** 

2.438 inches

**Body Width:** 

2.438 inches

**Body Height:** 

3.125 inches

# **Maximum Operating Temp:**

105.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Hermetically sealed

# **Mounting Facility Quantity:**

4 single group

**Mounting Method:** 

Threaded stud single group

Rating Method:

Electrical single component single winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

### **Winding Operating Current:**

900.0 milliamperes dc single component single winding

# Dc Resistance Rating In Ohms:

1.500 single component single winding

#### **Thread Series Designator:**

Unc single group

# NSN 5950-00-649-8343

Reactor - Page 2 of 2



i ei ii ii ii ai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-------------------------------------	----	--------	------	-----	-----------	--

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0