# NSN 5950-00-651-7916

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-651-7916

Reliability Indicat	or:
---------------------	-----

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.500 inches single mounting facility single center group

# **Mounting Hole Diameter:**

0.194 inches single group

# **Frequency Rating:**

350.0 hertz single component and 450.0 hertz single component

### Input-output Phase Relationship:

Single phase to single phase single component

#### **Body Length:**

2.250 inches

#### **Body Outside Diameter:**

0.250 inches

### **Installation For Which Designed:**

Indoor nonportable

### **End Application:**

Aircraft, hercules c-130, aircraft, hercules c-130f, aircraft, hercules kc-130, aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130)

# **Inclosure Type:**

Open

### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Flange single group and unthreaded hole single group

# **Winding Function And Quantity:**

1 secondary single component

### **Winding Operating Current:**

50.0 milliamperes ac single component single secondary

# **Criticality Code Justification:**

Feat

# **Special Features:**

Primary rated but not included. Weapon system essential.

# **Terminal Type And Quantity:**

2 bus (bar) conductor

# Shelf Life:

N/a

# **Unit Of Measure:**

--

# **Demilitarization:**

No

# NSN 5950-00-651-7916

Current Transformer - Page 2 of 2



Fiig:

A058b0