NSN 5950-00-652-5436

Saturable Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-652-5436

Reliability Indicator:
Not established
Overall Length:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.875 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.625 inches single mounting facility single center group
Overall Height:
1.094 inches
Overall Width:
1.969 inches
Frequency Rating:
90.0 hertz single component
Winding Shielding Method:
External inclosure single component
Body Height:
0.875 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
3 secondary and 1 control single component
Thready Qty Per Inch (tpi):
40 single group
Thread Size:
0.112 inches single group
Winding Operating Voltage:
6.00 ac volts and 7.00 ac volts single component 1st secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
10 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

NSN 5950-00-652-5436

Saturable Reactor - Page 2 of 2



Fiig:

A058b0