

View Online at <https://aerobasegroup.com/nsn/5950-00-655-0862>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility single center group

Impedance Rating In Ohms:

1000.0 single component single secondary

Primary To Secondary Turn Ratio:

1 to 4 single component

Pulse Repetition Rate:

400.0 hertz single component

Body Length:

4.812 inches

Body Width:

3.688 inches

Body Height:

5.625 inches

Inclosure Type:

Hermetically sealed with oil

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

16.0 amperes ac single component single secondary

Special Features:

Filament secondary winding 8.06 output 1.5 amp output 115 v primary winding voltage 400 cycles

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0