

View Online at <https://aerobasegroup.com/nsn/5950-00-655-0890>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.625 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

47.5 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

5.500 inches

Body Width:

5.000 inches

Body Height:

5.625 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

35.0 amperes ac single component single secondary

Winding Operating Voltage:

90.00 ac volts single component single primary and 95.00 ac volts single component single primary and 100.00 ac volts single component single primary and 105.00 ac volts single component single primary and 110.00 ac volts single component single primary and 115.00 ac volts single component single primary and 120.00 ac volts single component single primary

Terminal Type And Quantity:

8 tab, solder lug and 2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0