

View Online at <https://aerobasegroup.com/nsn/5950-00-658-5779>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.309 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Adjustment Device Drive Type:

Shaft single component

Body Length:

5.156 inches

Body Outside Diameter:

4.625 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

3 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary, variable autotransformer type single component

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

4.330 inches single mounting facility single center group

Winding Operating Current:

7.5 amperes ac single component single primary output

Winding Power Rating:

1.275 k1lovolt-amperes single component single primary output

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

3.750 inches single mounting facility single center group

Adjustment Method And Quantity:

1 adjustable control single component

Winding Operating Voltage:

120.00 ac pounds per hour wet single component single primary input

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0