

View Online at https://aerobasegroup.com/nsn/5950-00-658-5779

# **Reliability Indicator:**

Not established

# Mounting Hole Diameter:

0.309 inches single group

# Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

### Adjustment Device Drive Type:

Shaft single component

#### **Body Length:**

5.156 inches

#### Body Outside Diameter:

4.625 inches

#### Inclosure Type:

Fully enclosed

# Mounting Facility Quantity:

3 single group

# **Mounting Method:**

Unthreaded hole single group

### Winding Function And Quantity:

1 primary, variable autotransformer type single component

# Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

4.330 inches single mounting facility single center group

### Winding Operating Current:

7.5 amperes ac single component single primary output

### Winding Power Rating:

1.275 k1lovolt-amperes single component single primary output

### Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

3.750 inches single mounting facility single center group

### Adjustment Method And Quantity:

1 adjustable control single component

### Winding Operating Voltage:

120.00 ac pounds per hour wet single component single primary input

### Terminal Type And Quantity:

3 pin

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5950-00-658-5779

Power Autotransformer Transformer - Page 2 of 2

**Fiig:** A058b0

