# NSN 5950-00-660-4603

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-660-4603

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Overall Height:** 

2.312 inches

**Overall Width:** 

3.938 inches

Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:** 

4.688 inches

# **Maximum Operating Temp:**

85.0 degrees celsius

# Inclosure Type:

Open

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

# **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.164 inches single group

### **Winding Operating Current:**

5.77 amperes ac single component single secondary

#### **Winding Operating Voltage:**

416.00 ac volts single component single primary

#### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

9 tab, solder lug

# Shelf Life:

N/a

# **NSN 5950-00-660-4603**Power Transformer - Page 2 of 2



			ure:	

Demilitarization:

No

Fiig:

A058b0