NSN 5950-00-660-7378

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-660-7378

Reliability Indicator:
Not established
Frequency Rating:
380.0 hertz single component and 420.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
2.125 inches
Body Width:
1.438 inches
Body Height:
1.438 inches
Maximum Operating Temp:
85.0 degrees celsius
Distance Between Mounting Facility Centers:
1.625 inches single mounting facility single center group
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 4 secondary single component
Thready Qty Per Inch (tpi):
40 single group
Thread Size:
0.112 inches single group
Winding Operating Current:
6.0 milliamperes ac single component 4th secondary
Winding Operating Voltage:
26.00 ac volts single component 1st secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
11 turret
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-00-660-7378

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0