NSN 5950-00-660-7381

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-660-7381 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.375 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.500 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.219 inches single group |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure single component |
| Body Length: |
| 4.875 inches |
| Body Width: |
| 3.188 inches |
| Body Height: |
| 4.875 inches |
| Maximum Operating Temp: |
| 80.0 degrees celsius |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 15.5 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 230.00 ac pounds per hour wet single component single primary |
| Terminal Type And Quantity: |
| 4 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5950-00-660-7381

Power Transformer - Page 2 of 2



Fiig:

A058b0