

View Online at <https://aerobasegroup.com/nsn/5950-00-660-7920>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.500 inches single mounting facility single center group

Frequency Rating:

48.0 hertz single component and 62.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

1.7 kilovolt-ampere single component

Winding Shielding Method:

Internally shielded and brought out to primary terminal single component

Body Length:

10.531 inches

Body Width:

7.281 inches

Body Height:

6.781 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.3125 inches single group

Winding Operating Current:

160.0 milliamperes dc single component single secondary

Winding Operating Voltage:

117.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

3 threaded stud and 10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0