## NSN 5950-00-660-7920

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-660-7920

## **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

8.750 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

5.500 inches single mounting facility single center group

### Frequency Rating:

48.0 hertz single component and 62.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single component

## **Maximum Transformer Power Rating:**

1.7 kilovolt-ampere single component

### **Winding Shielding Method:**

Internally shielded and brought out to primary terminal single component

### **Body Length:**

10.531 inches

## **Body Width:**

7.281 inches

### **Body Height:**

6.781 inches

## **Maximum Operating Temp:**

105.0 degrees celsius

## Inclosure Type:

Hermetically sealed

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded stud single group

### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

## **Thread Size:**

0.3125 inches single group

## **Winding Operating Current:**

160.0 milliamperes dc single component single secondary

## **Winding Operating Voltage:**

117.00 ac volts single component single primary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

3 threaded stud and 10 tab, solder lug

## Shelf Life:

N/a

# NSN 5950-00-660-7920

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0