NSN 5950-00-660-7922

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-660-7922
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.000 inches single mounting facility single center group
Frequency Rating:
50.0 hertz single component and 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
6.032 inches
Body Width:
4.500 inches
Body Height:
4.500 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
22.0 amperes ac single component single secondary
Winding Operating Voltage:
5.00 ac pounds per hour wet single component single secondary
Special Features:
Case metal material
Terminal Type And Quantity:
4 standoff, threaded stud and 1 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A058b0