

View Online at <https://aerobasegroup.com/nsn/5950-00-660-7922>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component and 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

6.032 inches

**Body Width:**

4.500 inches

**Body Height:**

4.500 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

22.0 amperes ac single component single secondary

**Winding Operating Voltage:**

5.00 ac pounds per hour wet single component single secondary

**Special Features:**

Case metal material

**Terminal Type And Quantity:**

4 standoff, threaded stud and 1 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0