NSN 5950-00-660-7933

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-660-7933

Reliability Indicator:

Not established

Turn Quantity:

169 single component all winding

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.359 inches single mounting facility single center group and 2.391 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.578 inches single mounting facility single center group and 1.672 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

1.40 henry single component all winding

Frequency Rating:

800.0 hertz single component

Body Length:

Between 3.297 inches and 3.375 inches

Body Width:

Between 2.516 inches and 2.594 inches

Body Height:

Between 2.937 inches and 3.063 inches

Maximum Operating Temp:

105.0 degrees celsius

Winding Quantity:

2 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component all winding and winding turns single component all winding

Features Provided:

Tinned wire leads

Thread Size:

0.138 inches single group

Winding Conductor Size:

0.02010 inches american wire gage single component all winding

Winding Operating Current:

150.0 milliamperes dc single component all winding

Dc Resistance Rating In Ohms:

4.950 single component all winding

NSN 5950-00-660-7933 Reactor - Page 2 of 2



Thread Series Designator:
Unc single group
Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0