

View Online at <https://aerobasegroup.com/nsn/5950-00-660-7935>

**Reliability Indicator:**

Not established

**Turn Quantity:**

364-1/2 single component single winding

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.297 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.859 inches single mounting facility single center group

**Inductance Type:**

Swinging

**Inductance Rating:**

126.00 millihenries single component single winding and 130.00 millihenries single component single winding and 134.00 millihenries single component single winding and 138.00 millihenries single component single winding and 142.00 millihenries single component single winding

**Frequency Rating:**

400.0 hertz single component

**Body Length:**

3.062 inches

**Body Width:**

2.625 inches

**Body Height:**

4.250 inches

**Maximum Operating Temp:**

70.0 degrees celsius

**Winding Quantity:**

1 single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Rating Method:**

Electrical single component single winding and winding turns single component single winding

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.164 inches single group

**Winding Conductor Size:**

0.02535 inches american wire gage single component single winding

**Dc Resistance Rating In Ohms:**

3.440 single component single winding

**Special Features:**

Internal shield grounded to core and brought out to terminal

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0