

View Online at <https://aerobasegroup.com/nsn/5950-00-660-7935>

Reliability Indicator:

Not established

Turn Quantity:

364-1/2 single component single winding

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.297 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches single mounting facility single center group

Inductance Type:

Swinging

Inductance Rating:

126.00 millihenries single component single winding and 130.00 millihenries single component single winding and 134.00 millihenries single component single winding and 138.00 millihenries single component single winding and 142.00 millihenries single component single winding

Frequency Rating:

400.0 hertz single component

Body Length:

3.062 inches

Body Width:

2.625 inches

Body Height:

4.250 inches

Maximum Operating Temp:

70.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single winding and winding turns single component single winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Conductor Size:

0.02535 inches american wire gage single component single winding

Dc Resistance Rating In Ohms:

3.440 single component single winding

Special Features:

Internal shield grounded to core and brought out to terminal

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0