

View Online at <https://aerobasegroup.com/nsn/5950-00-671-6819>

**Reliability Indicator:**

Not established

**Turn Quantity:**

30 single component single secondary

**Inductance Rating:**

5.00 microhenries single component single secondary

**Frequency Rating:**

790.0 kilohertz single component

**Coil Form Type:**

Hollow single component

**Adjustment Device Drive Type:**

Slotted screw single component

**Body Length:**

2.125 inches

**Body Width:**

1.000 inches

**Body Height:**

1.000 inches

**Distance Between Mounting Facility Centers:**

1.375 inches single mounting facility single center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded hole single group

**Rating Method:**

Electrical single component single primary and winding turns single component single primary

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Winding Conductor Size:**

0.00397 inches american wire gage single component single primary

**Adjustment Method And Quantity:**

1 adjustable core single component

**Special Features:**

One 220 uuf capacitor, one 22000 ohm resistor, one variable resistor

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0