NSN 5950-00-672-3430

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-672-3430

| view Offilite at https://aerobasegroup.com/nsn/0330-00-072-0430 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.188 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.188 inches single mounting facility single center group |
| Frequency Rating: |
| 60.0 hertz single component and 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 1.625 inches |
| Body Width: |
| 1.625 inches |
| Body Height: |
| 2.375 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 100.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 21.00 ac volts single component single secondary and 23.00 ac volts single component single secondary and 25.00 ac volts single |
| component single secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-00-672-3430

Power Transformer - Page 2 of 2



Fiig:

A058b0