NSN 5950-00-674-1466

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-674-1466

Reliability Indicator:
lot established
Center To Center Distance Between Mounting Facilities Parallel To Length:
.500 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
.000 inches single mounting facility single center group
Frequency Rating:
0.0 hertz single component or 60.0 hertz single component
nput-output Phase Relationship:
Single phase to single phase single component
Vinding Shielding Method:
nternal shield grounded to inclosure single component
Body Length:
.375 inches
Body Width:
.250 inches
Body Height:
.375 inches
nclosure Type:
lermetically sealed
Iounting Facility Quantity:
single group
Iounting Method:
hreaded stud single group
Vinding Function And Quantity:
primary single component and 4 secondary single component
hready Qty Per Inch (tpi):
2 single group
hread Size:
.190 inches single group
Vinding Operating Current:
.0 amperes ac single component 2nd secondary
Vinding Operating Voltage:
.30 ac volts single component 2nd secondary
hread Series Designator:
Inf single group
erminal Type And Quantity:
4 standoff insulator
Shelf Life:
I/a
Init Of Measure:

NSN 5950-00-674-1466

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

