## NSN 5950-00-678-0348

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-678-0348
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.187 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.187 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
1.625 inches
Body Width:
1.625 inches
Body Height:
2.375 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
2.0 amperes ac single component single secondary
Winding Operating Voltage:
6.30 ac volts single component single secondary
Test Data Document:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
4 standoff, solder lug
Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5950-00-678-0348

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0