

View Online at <https://aerobasegroup.com/nsn/5950-00-681-2046>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 1.5 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

1.938 inches

Body Width:

1.812 inches

Body Height:

2.750 inches

Maximum Operating Temp:

131.0 degrees fahrenheit

End Application:

Underwater torpedo tubes, submarine ship control and navigation systems, aircraft, hawkeye e-2c, helicopter, sea king h-3, aircraft, orion p-3, missile, minuteman lgm-30, aircraft hercules c-130

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

1.5 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

24.00 ac volts single component single secondary

Special Features:

Weapons system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0