

View Online at <https://aerobasegroup.com/nsn/5950-00-681-2050>

**Reliability Indicator:**

Not established

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

2.953 inches

**Body Width:**

1.766 inches

**Body Height:**

4.500 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

3 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:**

1.250 inches single mounting facility single center group

**Winding Operating Current:**

676.0 milliamperes ac single component 3rd secondary

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

2.562 inches single mounting facility single center group

**Winding Operating Voltage:**

6.30 ac volts single component 1st secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0