

View Online at <https://aerobasegroup.com/nsn/5950-00-681-2050>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.953 inches

Body Width:

1.766 inches

Body Height:

4.500 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

3 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

1.250 inches single mounting facility single center group

Winding Operating Current:

676.0 milliamperes ac single component 3rd secondary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

2.562 inches single mounting facility single center group

Winding Operating Voltage:

6.30 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0