

View Online at <https://aerobasegroup.com/nsn/5950-00-681-2205>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.062 inches single mounting facility single center group

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

1.125 inches

Body Width:

1.406 inches

Body Height:

1.500 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

20.0 milliamperes ac single component all secondary

Winding Operating Voltage:

24.00 ac volts single component single primary and 115.00 ac volts single component single primary and 230.00 ac volts single component single primary

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0