

View Online at <https://aerobasegroup.com/nsn/5950-00-681-2217>

Reliability Indicator:

Not established

Overall Length:

3.062 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.297 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches single mounting facility single center group

Overall Height:

4.688 inches

Overall Width:

2.625 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Height:

4.250 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

70.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 tab, solder lug

Specification Data:

96906-ms90026 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0