

View Online at <https://aerobasegroup.com/nsn/5950-00-681-2217>

**Reliability Indicator:**

Not established

**Overall Length:**

3.062 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.297 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.859 inches single mounting facility single center group

**Overall Height:**

4.688 inches

**Overall Width:**

2.625 inches

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Height:**

4.250 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

70.0 milliamperes ac single component 3rd secondary

**Winding Operating Voltage:**

6.30 ac volts single component 2nd secondary

**Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

14 tab, solder lug

**Specification Data:**

96906-ms90026 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0