## NSN 5950-00-681-2996

Reactor - Page 1 of 2

Unc single group



View Online at https://aerobasegroup.com/nsn/5950-00-681-2996

Reliability Indicator:				
Not established				
Turn Quantity:				
2000 single component single winding				
Center To Center Distance Between Mounting Facilities Parallel To Length:				
2.281 inches single mounting facility single center group and 2.312 inches single mounting facility single center group				
Center To Center Distance Between Mounting Facilities Parallel To Width:				
1.843 inches single mounting facility single center group and 1.875 inches single mounting facility single center group				
Inductance Type:				
Fixed				
Inductance Rating:				
3.00 henry single component single winding				
Frequency Rating:				
2.4 kilohertz single component				
Body Length:				
3.187 inches				
Body Width:				
2.750 inches				
Body Height:				
4.437 inches				
Maximum Operating Temp:				
85.0 degrees celsius				
Winding Quantity:				
1 single component				
Inclosure Type:				
Hermetically sealed				
Mounting Facility Quantity:				
4 single group				
Mounting Method:				
Threaded stud single group				
Rating Method:				
Electrical single component single winding and winding turns single component single winding				
Thread Size:				
0.164 inches single group				
Winding Conductor Size:				
0.01003 inches american wire gage single component single winding				
Winding Operating Current:				
200.0 milliamperes dc single component single winding				
Dc Resistance Rating In Ohms:				
120.000 single component single winding				
Thread Series Designator:				

## NSN 5950-00-681-2996

Reactor - Page 2 of 2



Termin:	al Tyne	And (	Quantity:
	ai ivbe	Allu V	zuannıv.

2 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0