

View Online at <https://aerobasegroup.com/nsn/5950-00-681-6292>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

Frequency Rating:

370.0 hertz single component and 430.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

5.750 inches

Body Width:

5.125 inches

Body Height:

5.688 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

850.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

313.00 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0