## NSN 5950-00-681-7024

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-681-7024

| · · · · · · · · · · · · · · · · · · ·                                     |
|---|
| Overall Length:   |
| 3.125 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.750 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.375 inches single mounting facility single center group                 |
| Overall Height:   |
| 4.125 inches  |
| Overall Width:  |
| 2.812 inches  |
| Mounting Hole Diameter:   |
| 0.250 inches single group   |
| Frequency Rating:   |
| 50.0 hertz single component and 60.0 hertz single component               |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield brought out to terminal single component                  |
| Body Length:  |
| 3.125 inches  |
| Body Width:   |
| 2.812 inches  |
| Body Height:  |
| 4.125 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange single group and unthreaded hole single group                      |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Winding Operating Current:  |
| 500.0 milliamperes ac single component single secondary                   |
| Winding Operating Voltage:  |
| 27.50 ac pounds per hour wet single component single secondary            |
| Terminal Type And Quantity:   |
| 5 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5950-00-681-7024

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0