NSN 5950-00-683-3058

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-683-3058

| · |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.500 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.500 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.281 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 7.750 inches |
| Body Width: |
| 6.380 inches |
| Body Height: |
| 5.620 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 16 secondary single component |
| Terminal Type And Quantity: |
| 34 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |