## NSN 5950-00-683-3222

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-683-3222             |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.625 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 0.438 inches single mounting facility single center group                 |
| Mounting Hole Diameter:   |
| 0.188 inches single group   |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure single component                    |
| Body Length:  |
| 1.312 inches  |
| Body Width:   |
| 1.250 inches  |
| Body Height:  |
| 1.062 inches  |
| Inclosure Type:   |
| Open  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange single group and unthreaded hole single group                      |
| Winding Function And Quantity:  |
| 1 primary single component and 4 secondary single component               |
| Winding Operating Current:  |
| 10.0 milliamperes ac single component all secondary                       |
| Winding Operating Voltage:  |
| 26.00 ac pounds per hour wet single component all secondary               |
| Terminal Type And Quantity:   |
| 10 tab, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

Fiig:

A058b0