# NSN 5950-00-683-4429

Saturable Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-683-4429

## **Overall Length:**

3.625 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.700 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.800 inches single mounting facility single center group

#### **Overall Height:**

2.215 inches

**Overall Width:** 

2.308 inches

Frequency Rating:

400.0 hertz single component

#### Winding Shielding Method:

Internal shield grounded to inclosure single component

#### Inclosure Type:

Hermetically sealed

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

## Winding Function And Quantity:

4 primary single component

## Saturation Current Rating:

5.0 milliamperes

### Thready Qty Per Inch (tpi):

32 single group

## Thread Size:

0.188 inches single group

### Dc Resistance Rating In Ohms:

100.000 single component all control

### Winding Operating Voltage:

300.00 ac volts single component all primary

#### **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

# NSN 5950-00-683-4429

Saturable Reactor - Page 2 of 2

Fiig: A058b0

