# NSN 5950-00-683-6849

Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-683-6849

Reliability	Indicator:
-------------	------------

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

3.200 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

**Body Length:** 

5.300 inches

**Body Width:** 

4.000 inches

**Body Height:** 

2.800 inches

**Inclosure Type:** 

Open

**Mounting Facility Quantity:** 

4 single group

**Mounting Method:** 

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Winding Tap Location (non-core):

Multiple taps w/o center tap single component single primary output

## **Winding Operating Current:**

4.0 milliamperes ac single component single primary output and 5.0 milliamperes ac single component single primary output and 5.0 milliamperes ac single component single primary output and 6.0 milliamperes ac single component single primary output and 6.0 milliamperes ac single component single primary output and 6.0 milliamperes ac single component single primary output and 6.0 milliamperes ac single component single primary output and 6.0 milliamperes ac single component single primary output

# **Winding Power Rating:**

2.4 volts-amperes single component single primary input

#### Winding Operating Voltage:

380.00 ac pounds per hour wet single component single primary output and 397.00 ac pounds per hour wet single component single primary output and 414.00 ac pounds per hour wet single component single primary output and 432.00 ac pounds per hour wet single component single primary output and 450.00 ac pounds per hour wet single component single primary output and 470.00 ac pounds per hour wet single component single primary output and 490.00 ac pounds per hour wet single component single primary output

## **Terminal Type And Quantity:**

10 threaded stud

Shelf Life:

N/a

Unit Of Measure:

Domilitarization.

\_