

View Online at <https://aerobasegroup.com/nsn/5950-00-683-6958>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

55.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

3.188 inches

Body Width:

2.750 inches

Body Height:

3.500 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

5.0 amperes ac single component single secondary and 5.3 amperes ac single component single secondary

Winding Operating Voltage:

6.30 ac volts single component single secondary and 6.50 ac volts single component single secondary

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0