

View Online at <https://aerobasegroup.com/nsn/5950-00-683-7027>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

1.625 inches

Body Width:

1.438 inches

Body Height:

2.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

3 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

0.938 inches single mounting facility single center group

Winding Operating Current:

40.0 milliamperes ac single component single secondary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.188 inches single mounting facility single center group

Winding Operating Voltage:

26.00 ac volts single component single primary and 115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0