

View Online at <https://aerobasegroup.com/nsn/5950-00-683-7410>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.438 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Length:**

3.938 inches

**Body Width:**

3.375 inches

**Body Height:**

4.312 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

3.0 amperes ac single component 2nd secondary

**Winding Operating Voltage:**

6.30 ac volts single component 1st secondary

**Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

11 tab, solder lug

**Specification Data:**

96906-ms90028 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0