Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-686-6322

Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 4.940 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group Frequency Rating: 80.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 4.940 inches Body Width: 4.940 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Function And Quantity: 1 primary, variable autotransformer type single component Thread stud single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Mount of Measure: 		
Center To Center Distance Between Mounting Facilities Parallel To Length: 4.340 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group Frequency Rating: 80.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 4.940 inches Body Width: 4.940 inches Body Width: 4.940 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Thread stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Uty Pr Inch (tpi): 32 single group Minding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Stries Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: Na Unit Of Measure: Demilitarization:	Reliability Indicator:	
A 940 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group Frequency Rating: 50.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 4.940 inches Body Width: 4.900 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threade stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thread Yup Per Inch (tpi): 32 single group Muding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Winding Operating Voltage: 7. Ya Unc single group Terminal Type And Quantity: 7. tab, solder lug Shelf Life: Ya Unit Of Measure: - Demilitarization:	Not established	
Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group Frequency Rating: 80.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 4.940 inches Body Width: 4.000 inches Body Width: 4.000 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Stries Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Center To Center Distance Between Mounting Facilities Parallel To I	_ength:
4.000 inches single mounting facility single center group Frequency Rating: 80.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 4.940 inches Body Width: 4.940 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threade stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Munting Operating Current: 3.0 amprese ac single component single primary output Winding Operating Voltage: 8.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	4.940 inches single mounting facility single center group	
Frequency Rating: 80.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 4.940 inches Body Width: 4.000 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 1 single group Mounting Function And Quantity: 1 primary, variable autotransformer type single component Thread stud single group Winding Operating Current: 32 single group Winding Operating Current: 30 amperes ac single component single primary output Winding Operating Voltage: 8.50 ac volts single component single primary output Winding Operating Voltage: 8.10 ac volts single component single primary output Thread Size group Terminal Type And Quantity: 13 tab, solder lug <	Center To Center Distance Between Mounting Facilities Parallel To	Nidth:
so.0. herz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 4.940 inches Body Width: 4.940 inches Body Height: 5.150 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threade stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	4.000 inches single mounting facility single center group	
Input-output Phase Relationship: Single phase to single phase single component Body Length: 4.940 inches Body Width: 4.900 inches Body Width: 4.000 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: Na Unit Of Measure: Demilitarization:	Frequency Rating:	
Single phase to single phase single component Body Length: 4.940 inches Body Width: 4.900 inches Body Width: 4.000 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threadd stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit of Measure:	60.0 hertz single component	
Body Length: 4.940 inches Body Width: 4.000 inches Body Height: 5.150 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit of Measure: Demilitarization:	Input-output Phase Relationship:	
4.940 inches Body Width: 4.000 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Single phase to single phase single component	
Body Width: 4.000 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Sizeis Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Length:	
4.000 inches Body Height: 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Sizes 0.138 inches Single component single primary output Winding Operating Voltage: 8.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:	4.940 inches	
Body Height: 5.150 inches 5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Width:	
5.150 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	4.000 inches	
Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:	Body Height:	
Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: 	5.150 inches	
Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Inclosure Type:	
4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Hermetically sealed	
Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Mounting Facility Quantity:	
Threaded stud single group Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	4 single group	
Winding Function And Quantity: 1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Mounting Method:	
1 primary, variable autotransformer type single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Threaded stud single group	
Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Winding Function And Quantity:	
32 single group Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: 	1 primary, variable autotransformer type single component	
Thread Size: 0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Thready Qty Per Inch (tpi):	
0.138 inches single group Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: 	32 single group	
Winding Operating Current: 3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread Size:	
3.0 amperes ac single component single primary output Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:	0.138 inches single group	
Winding Operating Voltage: 6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Winding Operating Current:	
6.50 ac volts single component single primary output Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	3.0 amperes ac single component single primary output	
Thread Series Designator: Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Winding Operating Voltage:	
Unc single group Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	6.50 ac volts single component single primary output	
Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread Series Designator:	
3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Unc single group	
Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type And Quantity:	
Shelf Life: N/a Unit Of Measure: Demilitarization:	3 tab, solder lug	
Unit Of Measure: Demilitarization:	Shelf Life:	
 Demilitarization:	N/a	
 Demilitarization:	Unit Of Measure:	
	-	
	Demilitarization:	
	No	

NSN 5950-00-686-6322

Power Autotransformer Transformer - Page 2 of 2

Fiig: A058b0

